



Walk-Behind Tandem Rollers

MRH800 Series

The MRH800-Series tandem rollers feature a streamlined design that allows access to tighter areas. These versatile rollers are ideal for asphalt patching or compaction of granular soils.

- **Hydrostatic drive** provides smooth operation.
- **External vibrator** with permanently lubricated bearings to minimize service.
- **Standard drum chocks** to help roller when parked on a slope.
- **Available with either Honda gasoline or Yanmar diesel engines.**
- **Front bumper and work light** are standard.
- **Narrow profile** with less than one-inch wall clearance.
- **Plastic water tank** prevents rust.



MRH800GS:
Shown with 11-HP Honda gasoline engine*
(10-HP Yanmar diesel optional*)

Model**	Compact Force lbs. (kN)	Frequency VPM (Hz)	Drum Width in. (mm)	Overall Width in. (mm)	Grade-ability	Travel Speed mph (kph)	Engine*	Start Method	Fuel	Water Tank gal. (lt)	Operating Weight lb. (kg)
MRH800GS	5,300 (23.5)	3,300 (55.3)	25.6 (650)	27.2 (692)	35%	0-2 (0-3)	11-HP Honda GX390	Electric & Recoil	Gas	10.6 (40.3)	1,530 (694)
MRH800DS2	5,300 (23.5)	3,300 (55.3)	25.6 (650)	27.2 (692)	35%	0-2 (0-3)	10-HP Yanmar L100V	Electric & Recoil	Diesel	10.6 (40.3)	1,562 (709)



Easy access to hydraulic components and hydraulic filter.

* Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MultiQuip Inc. and its subsidiary companies makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy of the engine power rating. Users are advised to consult the engine manufacturer's owners manual and its website for specific information regarding the engine power rating.

** Battery not included.

© COPYRIGHT 2011, MULTIQUIP INC.



MULTIQUIP INC.
POST OFFICE BOX 6254
CARSON, CA 90749
310-537-3700 • 800-421-1244
FAX: 310-537-3927
E-MAIL: mq@multiquip.com
www.multiquip.com