



Dimensions

| | | |
|-------------------------------------|----------|-----------|
| A. Maximum Operating Height | 149.1 in | 3787.1 mm |
| B. Height | 77.8 in | 1976.1 mm |
| C. Angle of Departure | | 24.2° |
| D. Ground Clearance | 7.3 in | 185.4 mm |
| E. Wheelbase | 42.6 in | 1082 mm |
| F. Length without Attachment | 104.6 in | 2656.8 mm |
| G. Length with Standard Bucket | 133 in | 3378.2 mm |
| H. Rollback Angle | | 30° |
| I. Dump Height @ Max Lift | 86.8 in | 2204.7 mm |
| J. Reach @ Maximum Height | 17 in | 431.8 mm |
| K. Height to Bucket Hinge Pin | 114.5 in | 2908.3 mm |
| L. Dump Angle @ Max Lift | | 42° |
| M. Rollback Angle @ Full Height | | 97° |
| N. Width (with bucket) | 68 in | 1727.2 mm |
| O. Turning Radius | 80 in | 2032 mm |
| P. Width - Centerline to Centerline | 54.1 in | 1374.1 mm |
| Q. Width | 64.7 in | 1643.4 mm |

Specifications

| | | |
|--------------------------|----------|-----------|
| Horsepower | 61 hp | 45.5 kw |
| Fuel Type | | Diesel |
| Fuel Capacity | 24.8 gal | 93.9 L |
| Rated Operating Capacity | 1750 lb | 793.8 kg |
| Operating Weight | 6213 lb | 2818.2 kg |
| Travel Speed - Low | 7.4 mph | 11.9 km/h |
| Travel Speed - High | 11 mph | 17.7 km/h |

S550